REPORT OF ANNUAL INSPECTION OF CCR SURFACE IMPOUNDMENT FACILITY NAME: Miller Steam Plant Ash Pond Dam OWNER/OPERATOR OF FACILITY: Alabama Power Company INSPECTION DATE: October 15, 2020 INSPECTION ENGINEER: Jacob A. Jordan, P.E. (Alabama P.E. License #25093) Southern Company Services – Principal Engineer, Fossil Dam Safety ANY CHANGES IN GEOMETRY OF THE IMPOUNDING ANY CHANGES IN GEOMETRY OF THE IMPOUNDING INSPECTION? (IF YES, DESCRIBE): LOCATION AND TYPE OF EXISTING INSTRUMENTATION See attached Table 1 See attached Table 2 (deformation monuments not applicable) APPROXIMATE MINIMUM, MAXIMUM AND PRESENT DEPTH AND ELEVATION OF THE IMPOUNDED WATER SINCE PREVIOUS ANNUAL INSPECTION MIN. DEPTH: less than 1 foot MAX. DEPTH: 76 ft MAX. DEPTH: 76 ft APPROXIMATE MINIMUM, MAXIMUM AND PRESENT DEPTH AND ELEVATION: EL 419 ft APPROXIMATE MINIMUM, MAXIMUM AND PRESENT DEPTH AND ELEVATION OF CCR SINCE PREVIOUS ANNUAL INSPECTION. MIN. DEPTH: less than 1 ft MAX. DEPTH: 60 ft PRESENT DEPTH: up to 60 feet MIN. ELEVATION: EL 300 ft (est.) MAX. DEPTH: 60 ft PRESENT DEPTH: up to 60 feet MIN. ELEVATION: EL 300 ft (est.) MAX. DEPTH: 60 ft PRESENT DEPTH: up to 60 feet MIN. ELEVATION: EL 300 ft (est.) MAX. DEPTH: 60 ft PRESENT DEPTH: up to 60 feet MIN. ELEVATION: EL 300 ft (est.) MAX. ELEVATION: EL 445 ft PRESENT DEPTH: up to 60 feet MIN. ELEVATION: EL 300 ft (est.) MAX. ELEVATION: EL 445 ft PRESENT DEPTH: up to 60 feet MIN. ELEVATION: EL 300 ft (est.) MAX. ELEVATION: EL 445 ft PRESENT DEPTH: up to 60 feet MIN. ELEVATION: EL 300 ft (est.) MAX. ELEVATION: EL 445 ft PRESENT DEPTH: up to 60 feet MIN. ELEVATION: EL 300 ft (est.) MAX. ELEVATION: EL 445 ft PRESENT DEPTH: up to 60 feet MIN. ELEVATION: EL 300 ft (est.) MAX. ELEVATION: EL 445 ft PRESENT DEPTH: up to 60 feet MIN. ELEVATION: EL 300 ft (est.) MAX. ELEVATION: EL 445 ft PRESENT DEPTH: up to 60 feet MIN. ELEVATION: EL 300 ft (est.) MAX. ELEVATION: EL 445 ft PRESENT DEPTH: up to 60 feet					
OWNER/OPERATOR OF FACILITY: Alabama Power Company INSPECTION DATE: October 15, 2020 INSPECTING ENGINEER: Jacob A. Jordan, P.E. (Alabama P.E. License #25093) Southern Company Services – Principal Engineer, Fossil Dam Safety ANY CHANGES IN GEOMETRY OF THE IMPOUNDING STRUCTURE SINCE THE PREVIOUS ANNUAL INSPECTION? (IF YES, DESCRIBE): LOCATION AND TYPE OF EXISTING INSTRUMENTATION See attached Table 1 MAXIMUM RECORDED READING OF EACH INSTRUMENT SINCE PREVIOUS ANNUAL INSPECTION APPROXIMATE MINIMUM, MAXIMUM AND PRESENT DEPTH AND ELEVATION OF THE IMPOUNDED WATER SINCE PREVIOUS ANNUAL INSPECTION MIN. DEPTH: less than 1 foot MAX. DEPTH: 76 ft PRESENT DEPTH: up to 75 feet MIN. ELEVATION: EL 419 ft MAX. ELEVATION: EL 420.5 ft PRESENT. ELEVATION: EL 419 ft APPROXIMATE MINIMUM, MAXIMUM AND PRESENT DEPTH AND ELEVATION OF CCR SINCE PREVIOUS ANNUAL INSPECTION. MIN. DEPTH: less than 1 ft MAX. DEPTH: 60 ft PRESENT DEPTH: up to 60 feet MIN. ELEVATION: EL 300 ft (est.) MAX. DEPTH: 60 ft PRESENT DEPTH: up to 60 feet MIN. ELEVATION: EL 300 ft (est.) MAX. ELEVATION: EL 445 ft PRESENT ELEVATION: up to EL 445 APPROXIMATE STORAGE CAPACITY OF IMPOUNDING STRUCTURE AT TIME OF 1000 MAX. APPROXIMATE STORAGE CAPACITY OF IMPOUNDING STRUCTURE AT TIME OF 1000 MAX. APPROXIMATE STORAGE CAPACITY OF					
INSPECTION DATE: October 15, 2020 INSPECTING ENGINEER: Jacob A. Jordan, P.E. (Alabama P.E. License #25093) Southern Company Services – Principal Engineer, Fossil Dam Safety ANY CHANGES IN GEOMETRY OF THE IMPOUNDING NO STRUCTURE SINCE THE PREVIOUS ANNUAL INSPECTION? (IF YES, DESCRIBE): LOCATION AND TYPE OF EXISTING INSTRUMENTATION See attached Table 1 MAXIMUM RECORDED READING OF EACH INSTRUMENT SINCE PREVIOUS ANNUAL INSPECTION APPROXIMATE MINIMUM, MAXIMUM AND PRESENT DEPTH AND ELEVATION OF THE IMPOUNDED WATER SINCE PREVIOUS ANNUAL INSPECTION MIN. DEPTH: less than 1 foot MAX. DEPTH: 76 ft PRESENT DEPTH: up to 75 feet MIN. ELEVATION: EL 419 ft MAX. ELEVATION: EL 420.5 ft PRESENT. ELEVATION EL 419 ft APPROXIMATE MINIMUM, MAXIMUM AND PRESENT DEPTH AND ELEVATION OF CCR SINCE PREVIOUS ANNUAL INSPECTION. MIN. DEPTH: less than 1 ft MAX. DEPTH: 60 ft PRESENT DEPTH: up to 60 feet MIN. ELEVATION: EL 300 ft (est.) MAX. ELEVATION: EL 445 ft PRESENT ELEVATION: up to EL 445 APPROXIMATE STORAGE CAPACITY OF IMPOUNDING STRUCTURE AT TIME OF INSPECTION. APPROXIMATE VOLUME OF IMPOUNDED WATER: 1,150,000 CCR: 19 500 000 vri3*					
Southern Company Services – Principal Engineer, Fossil Dam Safety ANY CHANGES IN GEOMETRY OF THE IMPOUNDING STRUCTURE SINCE THE PREVIOUS ANNUAL INSPECTION? (IF YES, DESCRIBE): LOCATION AND TYPE OF EXISTING INSTRUMENTATION MAXIMUM RECORDED READING OF EACH INSTRUMENT SINCE PREVIOUS ANNUAL INSPECTION APPROXIMATE MINIMUM, MAXIMUM AND PRESENT DEPTH AND ELEVATION OF THE IMPOUNDED WATER SINCE PREVIOUS ANNUAL INSPECTION MIN. DEPTH: less than 1 foot MAX. DEPTH: 76 ft PRESENT DEPTH: up to 75 feet MIN. ELEVATION: EL 419 ft MAX. ELEVATION: EL 420.5 ft PRESENT. ELEVATION OF CCR SINCE PREVIOUS ANNUAL INSPECTION. MIN. DEPTH: less than 1 ft MAX. DEPTH: 60 ft PRESENT DEPTH: up to 60 feet MIN. ELEVATION: EL 300 ft (est.) MAX. ELEVATION: EL 445 ft PRESENT ELEVATION: up to 60 feet MIN. ELEVATION: EL 300 ft (est.) MAX. ELEVATION: EL 445 ft PRESENT ELEVATION: up to EL 445 APPROXIMATE STORAGE CAPACITY OF IMPOUNDING STRUCTURE AT TIME OF 1000 MATER: 1,150,000 CCR: 19 500 000 wd3*					
Southern Company Services – Principal Engineer, Fossil Dam Safety ANY CHANGES IN GEOMETRY OF THE IMPOUNDING STRUCTURE SINCE THE PREVIOUS ANNUAL INSPECTION? (IF YES, DESCRIBE): LOCATION AND TYPE OF EXISTING INSTRUMENTATION See attached Table 1 MAXIMUM RECORDED READING OF EACH INSTRUMENT SINCE PREVIOUS ANNUAL INSPECTION APPROXIMATE MINIMUM, MAXIMUM AND PRESENT DEPTH AND ELEVATION OF THE IMPOUNDED WATER SINCE PREVIOUS ANNUAL INSPECTION MIN. DEPTH: less than 1 foot MAX. DEPTH: 76 ft PRESENT DEPTH: up to 75 feet MIN. ELEVATION: EL 419 ft MAX. ELEVATION: EL 420.5 ft PRESENT. ELEVATION: EL 419 ft APPROXIMATE MINIMUM, MAXIMUM AND PRESENT DEPTH AND ELEVATION OF CCR SINCE PREVIOUS ANNUAL INSPECTION. MIN. DEPTH: less than 1 ft MAX. DEPTH: 60 ft PRESENT DEPTH: up to 60 feet MIN. ELEVATION: EL 300 ft (est.) MAX. ELEVATION: EL 445 ft PRESENT DEPTH: up to 60 feet MIN. ELEVATION: EL 300 ft (est.) MAX. ELEVATION: EL 445 ft PRESENT ELEVATION: up to EL 445 APPROXIMATE STORAGE CAPACITY OF IMPOUNDING STRUCTURE AT TIME OF 12,000,000 yd3* INSPECTION. APPROXIMATE VOLUME OF IMPOUNDED WATER: 1,150,000 CCR: 19 500 000 yd3*					
ANY CHANGES IN GEOMETRY OF THE IMPOUNDING STRUCTURE SINCE THE PREVIOUS ANNUAL INSPECTION? (IF YES, DESCRIBE): LOCATION AND TYPE OF EXISTING INSTRUMENTATION MAXIMUM RECORDED READING OF EACH INSTRUMENT SINCE PREVIOUS ANNUAL INSPECTION APPROXIMATE MINIMUM, MAXIMUM AND PRESENT DEPTH AND ELEVATION OF THE IMPOUNDED WATER SINCE PREVIOUS ANNUAL INSPECTION MIN. DEPTH: less than 1 foot MAX. DEPTH: 76 ft PRESENT DEPTH: up to 75 feet MIN. ELEVATION: EL 419 ft APPROXIMATE MINIMUM, MAXIMUM AND PRESENT DEPTH AND ELEVATION OF CCR SINCE PREVIOUS ANNUAL INSPECTION. MIN. DEPTH: less than 1 ft MAX. ELEVATION: EL 420.5 ft PRESENT. ELEVATION: EL 419 ft APPROXIMATE MINIMUM, MAXIMUM AND PRESENT DEPTH AND ELEVATION OF CCR SINCE PREVIOUS ANNUAL INSPECTION. MIN. DEPTH: less than 1 ft MAX. DEPTH: 60 ft PRESENT DEPTH: up to 60 feet MIN. ELEVATION: EL 300 ft (est.) MAX. ELEVATION: EL 445 ft PRESENT DEPTH: up to 60 feet MIN. ELEVATION: EL 300 ft (est.) MAX. ELEVATION: EL 445 ft PRESENT ELEVATION: up to EL 445 APPROXIMATE STORAGE CAPACITY OF IMPOUNDING STRUCTURE AT TIME OF INSPECTION. APPROXIMATE VOLUME OF IMPOUNDED WATER: 1,150,000 CCR: 19 500 000 vd ^{3*}					
STRUCTURE SINCE THE PREVIOUS ANNUAL INSPECTION? (IF YES, DESCRIBE): LOCATION AND TYPE OF EXISTING INSTRUMENTATION MAXIMUM RECORDED READING OF EACH INSTRUMENT SINCE PREVIOUS ANNUAL INSPECTION APPROXIMATE MINIMUM, MAXIMUM AND PRESENT DEPTH AND ELEVATION OF THE IMPOUNDED WATER SINCE PREVIOUS ANNUAL INSPECTION MIN. DEPTH: less than 1 foot MAX. DEPTH: 76 ft PRESENT DEPTH: up to 75 feet MIN. ELEVATION: EL 419 ft MAX. ELEVATION: EL 420.5 ft PRESENT. ELEVATION: EL 419 ft APPROXIMATE MINIMUM, MAXIMUM AND PRESENT DEPTH AND ELEVATION OF CCR SINCE PREVIOUS ANNUAL INSPECTION. MIN. DEPTH: less than 1 ft MAX. DEPTH: 60 ft PRESENT DEPTH: up to 60 feet MIN. ELEVATION: EL 300 ft (est.) MAX. ELEVATION: EL 445 ft PRESENT ELEVATION: up to EL 445 APPROXIMATE STORAGE CAPACITY OF IMPOUNDING STRUCTURE AT TIME OF INSPECTION. APPROXIMATE VOLUME OF IMPOUNDED WATER: 1,150,000 CCR: 19 500 000 vd ^{3*}					
LOCATION AND TYPE OF EXISTING INSTRUMENTATION MAXIMUM RECORDED READING OF EACH INSTRUMENT SINCE PREVIOUS ANNUAL INSPECTION APPROXIMATE MINIMUM, MAXIMUM AND PRESENT DEPTH AND ELEVATION OF THE IMPOUNDED WATER SINCE PREVIOUS ANNUAL INSPECTION MIN. DEPTH: less than 1 foot MAX. DEPTH: 76 ft PRESENT DEPTH: up to 75 feet MIN. ELEVATION: EL 419 ft MAX. ELEVATION: EL 420.5 ft PRESENT. ELEVATION: EL 419 ft APPROXIMATE MINIMUM, MAXIMUM AND PRESENT DEPTH AND ELEVATION OF CCR SINCE PREVIOUS ANNUAL INSPECTION. MIN. DEPTH: less than 1 ft MAX. DEPTH: 60 ft PRESENT DEPTH: up to 60 feet MIN. ELEVATION: EL 300 ft (est.) MAX. ELEVATION: EL 445 ft PRESENT ELEVATION: up to EL 445 APPROXIMATE STORAGE CAPACITY OF IMPOUNDING STRUCTURE AT TIME OF INSPECTION. APPROXIMATE VOLUME OF IMPOUNDED WATER: 1,150,000 CCR: 19 500 000 vd ^{3*}					
LOCATION AND TYPE OF EXISTING INSTRUMENTATION MAXIMUM RECORDED READING OF EACH INSTRUMENT SINCE PREVIOUS ANNUAL INSPECTION APPROXIMATE MINIMUM, MAXIMUM AND PRESENT DEPTH AND ELEVATION OF THE IMPOUNDED WATER SINCE PREVIOUS ANNUAL INSPECTION MIN. DEPTH: less than 1 foot MAX. DEPTH: 76 ft PRESENT DEPTH: up to 75 feet MIN. ELEVATION: EL 419 ft MAX. ELEVATION: EL 420.5 ft PRESENT. ELEVATION: EL 419 ft APPROXIMATE MINIMUM, MAXIMUM AND PRESENT DEPTH AND ELEVATION OF CCR SINCE PREVIOUS ANNUAL INSPECTION. MIN. DEPTH: less than 1 ft MAX. DEPTH: 60 ft PRESENT DEPTH: up to 60 feet MIN. ELEVATION: EL 300 ft (est.) MAX. ELEVATION: EL 445 ft PRESENT ELEVATION: up to EL 445 APPROXIMATE STORAGE CAPACITY OF IMPOUNDING STRUCTURE AT TIME OF 122,000,000 yd³* CCR: 19 500 000 yd³*					
MAXIMUM RECORDED READING OF EACH INSTRUMENT SINCE PREVIOUS ANNUAL INSPECTION APPROXIMATE MINIMUM, MAXIMUM AND PRESENT DEPTH AND ELEVATION OF THE IMPOUNDED WATER SINCE PREVIOUS ANNUAL INSPECTION MIN. DEPTH: less than 1 foot MAX. DEPTH: 76 ft PRESENT DEPTH: up to 75 feet MIN. ELEVATION: EL 419 ft MAX. ELEVATION: EL 420.5 ft PRESENT. ELEVATION: EL 419 ft APPROXIMATE MINIMUM, MAXIMUM AND PRESENT DEPTH AND ELEVATION OF CCR SINCE PREVIOUS ANNUAL INSPECTION. MIN. DEPTH: less than 1 ft MAX. DEPTH: 60 ft PRESENT DEPTH: up to 60 feet MIN. ELEVATION: EL 300 ft (est.) MAX. ELEVATION: EL 445 ft PRESENT ELEVATION: up to EL 445 APPROXIMATE STORAGE CAPACITY OF IMPOUNDING STRUCTURE AT TIME OF 122,000,000 yd3* APPROXIMATE VOLUME OF IMPOUNDED WATER: 1,150,000 CCR: 19 500 000 yd3*					
MAXIMUM RECORDED READING OF EACH INSTRUMENT SINCE PREVIOUS ANNUAL INSPECTION APPROXIMATE MINIMUM, MAXIMUM AND PRESENT DEPTH AND ELEVATION OF THE IMPOUNDED WATER SINCE PREVIOUS ANNUAL INSPECTION MIN. DEPTH: less than 1 foot MAX. DEPTH: 76 ft PRESENT DEPTH: up to 75 feet MIN. ELEVATION: EL 419 ft MAX. ELEVATION: EL 420.5 ft PRESENT. ELEVATION: EL 419 ft APPROXIMATE MINIMUM, MAXIMUM AND PRESENT DEPTH AND ELEVATION OF CCR SINCE PREVIOUS ANNUAL INSPECTION. MIN. DEPTH: less than 1 ft MAX. DEPTH: 60 ft PRESENT DEPTH: up to 60 feet MIN. ELEVATION: EL 300 ft (est.) MAX. ELEVATION: EL 445 ft PRESENT ELEVATION: up to EL 445 APPROXIMATE STORAGE CAPACITY OF IMPOUNDING STRUCTURE AT TIME OF 122,000,000 yd3* APPROXIMATE VOLUME OF IMPOUNDED WATER: 1,150,000 CCR: 19 500 000 yd3*					
MAXIMUM RECORDED READING OF EACH INSTRUMENT SINCE PREVIOUS ANNUAL INSPECTION APPROXIMATE MINIMUM, MAXIMUM AND PRESENT DEPTH AND ELEVATION OF THE IMPOUNDED WATER SINCE PREVIOUS ANNUAL INSPECTION MIN. DEPTH: less than 1 foot MAX. DEPTH: 76 ft PRESENT DEPTH: up to 75 feet MIN. ELEVATION: EL 419 ft MAX. ELEVATION: EL 420.5 ft PRESENT. ELEVATION: EL 419 ft APPROXIMATE MINIMUM, MAXIMUM AND PRESENT DEPTH AND ELEVATION OF CCR SINCE PREVIOUS ANNUAL INSPECTION. MIN. DEPTH: less than 1 ft MAX. DEPTH: 60 ft PRESENT DEPTH: up to 60 feet MIN. ELEVATION: EL 300 ft (est.) MAX. ELEVATION: EL 445 ft PRESENT ELEVATION: up to EL 445 APPROXIMATE STORAGE CAPACITY OF IMPOUNDING STRUCTURE AT TIME OF 122,000,000 yd3* APPROXIMATE VOLUME OF IMPOUNDED WATER: 1,150,000 CCR: 19 500 000 yd3*					
PREVIOUS ANNUAL INSPECTION APPROXIMATE MINIMUM, MAXIMUM AND PRESENT DEPTH AND ELEVATION OF THE IMPOUNDED WATER SINCE PREVIOUS ANNUAL INSPECTION MIN. DEPTH: less than 1 foot MAX. DEPTH: 76 ft PRESENT DEPTH: up to 75 feet MIN. ELEVATION: EL 419 ft MAX. ELEVATION: EL 420.5 ft PRESENT. ELEVATION: EL 419 ft APPROXIMATE MINIMUM, MAXIMUM AND PRESENT DEPTH AND ELEVATION OF CCR SINCE PREVIOUS ANNUAL INSPECTION. MIN. DEPTH: less than 1 ft MAX. DEPTH: 60 ft PRESENT DEPTH: up to 60 feet MIN. ELEVATION: EL 300 ft (est.) MAX. ELEVATION: EL 445 ft PRESENT ELEVATION: up to EL 445 APPROXIMATE STORAGE CAPACITY OF IMPOUNDING STRUCTURE AT TIME OF 22,000,000 yd³* APPROXIMATE VOLUME OF IMPOUNDED WATER: 1,150,000 CCR: 19 500,000 yd³*					
APPROXIMATE MINIMUM, MAXIMUM AND PRESENT DEPTH AND ELEVATION OF THE IMPOUNDED WATER SINCE PREVIOUS ANNUAL INSPECTION MIN. DEPTH: less than 1 foot MAX. DEPTH: 76 ft PRESENT DEPTH: up to 75 feet MIN. ELEVATION: EL 419 ft MAX. ELEVATION: EL 420.5 ft PRESENT. ELEVATION: EL 419 ft APPROXIMATE MINIMUM, MAXIMUM AND PRESENT DEPTH AND ELEVATION OF CCR SINCE PREVIOUS ANNUAL INSPECTION. MIN. DEPTH: less than 1 ft MAX. DEPTH: 60 ft PRESENT DEPTH: up to 60 feet MIN. ELEVATION: EL 300 ft (est.) MAX. ELEVATION: EL 445 ft PRESENT ELEVATION: up to EL 445 APPROXIMATE STORAGE CAPACITY OF IMPOUNDING STRUCTURE AT TIME OF 22,000,000 yd³* APPROXIMATE VOLUME OF IMPOUNDED WATER: 1,150,000 CCR: 19 500,000 yd³*					
MIN. DEPTH: less than 1 foot MAX. DEPTH: 76 ft PRESENT DEPTH: up to 75 feet MIN. ELEVATION: EL 419 ft MAX. ELEVATION: EL 420.5 ft PRESENT. ELEVATION: EL 419 ft APPROXIMATE MINIMUM, MAXIMUM AND PRESENT DEPTH AND ELEVATION OF CCR SINCE PREVIOUS ANNUAL INSPECTION. MIN. DEPTH: less than 1 ft MAX. DEPTH: 60 ft PRESENT DEPTH: up to 60 feet MIN. ELEVATION: EL 300 ft (est.) MAX. ELEVATION: EL 445 ft PRESENT ELEVATION: up to EL 445 APPROXIMATE STORAGE CAPACITY OF IMPOUNDING STRUCTURE AT TIME OF INSPECTION. APPROXIMATE VOLUME OF IMPOUNDED WATER: 1,150,000 CCR: 19 500 000 vd3*					
MIN. DEPTH: less than 1 foot MAX. DEPTH: 76 ft PRESENT DEPTH: up to 75 feet MIN. ELEVATION: EL 419 ft MAX. ELEVATION: EL 420.5 ft PRESENT. ELEVATION: EL 419 ft APPROXIMATE MINIMUM, MAXIMUM AND PRESENT DEPTH AND ELEVATION OF CCR SINCE PREVIOUS ANNUAL INSPECTION. MIN. DEPTH: less than 1 ft MAX. DEPTH: 60 ft PRESENT DEPTH: up to 60 feet MIN. ELEVATION: EL 300 ft (est.) MAX. ELEVATION: EL 445 ft PRESENT ELEVATION: up to EL 445 APPROXIMATE STORAGE CAPACITY OF IMPOUNDING STRUCTURE AT TIME OF INSPECTION. APPROXIMATE VOLUME OF IMPOUNDED WATER: 1,150,000 CCR: 19 500 000 vd ^{3*}					
MIN. ELEVATION: EL 419 ft APPROXIMATE MINIMUM, MAXIMUM AND PRESENT DEPTH AND ELEVATION OF CCR SINCE PREVIOUS ANNUAL INSPECTION. MIN. DEPTH: less than 1 ft MAX. DEPTH: 60 ft PRESENT DEPTH: up to 60 feet MIN. ELEVATION: EL 300 ft (est.) MAX. ELEVATION: EL 445 ft PRESENT ELEVATION: up to EL 445 APPROXIMATE STORAGE CAPACITY OF IMPOUNDING STRUCTURE AT TIME OF INSPECTION. APPROXIMATE VOLUME OF IMPOUNDED WATER: 1,150,000 CCR: 19 500 000 vd3*					
APPROXIMATE MINIMUM, MAXIMUM AND PRESENT DEPTH AND ELEVATION OF CCR SINCE PREVIOUS ANNUAL INSPECTION. MIN. DEPTH: less than 1 ft					
MIN. DEPTH: less than 1 ft MAX. DEPTH: 60 ft PRESENT DEPTH: up to 60 feet MIN. ELEVATION: EL 300 ft (est.) MAX. ELEVATION: EL 445 ft PRESENT ELEVATION: up to EL 445 APPROXIMATE STORAGE CAPACITY OF IMPOUNDING STRUCTURE AT TIME OF INSPECTION. APPROXIMATE VOLUME OF IMPOUNDED WATER: 1,150,000 CCR: 19 500 000 vd ^{3*}					
MIN. DEPTH: less than 1 ft					
MIN. ELEVATION: EL 300 ft (est.) MAX. ELEVATION: EL 445 ft PRESENT ELEVATION: up to EL 445 APPROXIMATE STORAGE CAPACITY OF IMPOUNDING STRUCTURE AT TIME OF INSPECTION. APPROXIMATE VOLUME OF IMPOUNDED WATER: 1,150,000 CCR: 19 500 000 yd3*					
APPROXIMATE STORAGE CAPACITY OF IMPOUNDING STRUCTURE AT TIME OF 22,000,000 yd³* INSPECTION. APPROXIMATE VOLUME OF IMPOUNDED WATER: 1,150,000 CCR: 19 500,000 yd³*					
IMPOUNDING STRUCTURE AT TIME OF 22,000,000 yd³* INSPECTION. APPROXIMATE VOLUME OF IMPOUNDED WATER: 1,150,000 CCR: 19 500,000 yd³*					
INSPECTION. APPROXIMATE VOLUME OF IMPOUNDED WATER: 1,150,000 CCR: 19 500 000 vd3*					
APPROXIMATE VOLUME OF IMPOUNDED WATER: 1,150,000 CCR: 19 500 000 vd ³ *					
CCR* 19 500 000 Va**					
WATER AND COR ATTIME OF INSPECTION 13*					
WATER AND CCR AT TIME OF INSPECTION yas*					
ANY APPEARANCE OF AN ACTUAL OR POTENTIAL STRUCTURAL					
WEAKNESS OF THE CCR UNIT, IN ADDITION TO ANY EXISTING					
CONDITIONS THAT ARE DISRUPTING OR HAVE THE POTENTIAL NO					
TO DISRUPT THE OPERATION AND SAFETY OF THE CCR UNIT					
AND APPURTENANT STRUCTURES?					
(IF YES, DESCRIBE):					
ANY OTHER CHANGE(S) WHICH MAY HAVE AFFECTED THE					
STABILITY OR OPERATION SINCE THE PREVIOUS ANNUAL NO					
INSPECTION?					
(IF YES, DESCRIBE):					

^{*}Volume figures are estimated derived from available information.

Based on the results of my inspection and review of the data provided, it is my professional opinion that the report has been completed in accordance with 40 CFR 257.83(b) and ADEM Admin. Code r. 335-13-15-.05(4)(b).

Jacob A. Jordan, P.E.

No. 25093
PROFESSIONAL

ENGINEER

OB A JORDAN

Date

TABLE 1: INSTRUMENTATION TYPE AND LOCATION – MILLER ASH POND		
INSTRUMENT NUMBER	INSTRUMENT TYPE	LOCATION
P-1	Piezometer	Crest (Top) of Embankment, Right (North) Portion of Dam
P-2	Piezometer	Crest of Embankment, Right Portion of Dam
P-3	Piezometer	Crest of Embankment, Right Portion of Dam
P-4	Piezometer	Crest of Embankment, Center of Dam
P-5	Piezometer	Crest of Embankment, Center of Dam
P-6	Piezometer	Toe (Bottom) of Dam, Right Portion of Dam
P-7	Piezometer	Toe of Dam, Right Portion of Dam
P-8	Piezometer	Toe of Dam, Right Portion of Dam
PA-1	Piezometer	Crest of Dam, Left (South) Portion of Dam
PA-2	Piezometer	Crest of Dam, Left Portion of Dam
PA-4	Piezometer	Crest of Dam, Center of Dam
PA-5	Piezometer	Crest of Dam, Center of Dam
PA-6	Piezometer	Crest of Dam, Center of Dam
PA-7	Piezometer	Crest of Dam, Center of Dam
PA-8	Piezometer	Crest of Dam, Center of Dam
PA-9	Piezometer	Crest of Dam, Center of Dam
PA-10	Piezometer	Toe of Dam, Right Portion of Dam
PA-11	Piezometer	Toe of Dam, Right Portion of Dam
EX-1	Piezometer	Crest of Dam, Right Abutment of Dam
EX-2	Piezometer	Right Abutment of Dam
EX-3	Piezometer	Crest of Dam, Right Portion of Dam
EX-4	Piezometer	Crest of Dam, Right Portion of Dam
SM-001	Deformation Survey Monument (Vertical and Horizontal)	Crest of Dam, Left Abutment
SM-002	Deformation Survey Monument (Vertical and Horizontal)	Crest of Dam, Left Portion of Dam
SM-003	Deformation Survey Monument (Vertical and Horizontal)	Crest of Dam, Left Portion of Dam
SM-004	Deformation Survey Monument (Vertical and Horizontal)	Crest of Dam, Center of Dam
SM-005	Deformation Survey Monument (Vertical and Horizontal)	Crest of Dam, Center of Dam
SM-006	Deformation Survey Monument (Vertical and Horizontal)	Crest of Dam, Center of Dam
SM-007	Deformation Survey Monument (Vertical and Horizontal)	Crest of Dam, Right Portion of Dam

TABLE 2: MAXIMUM RECORDED READINGS OF EACH INSTRUMENT SINCE PREVIOUS ANNUAL INSPECTION

INSTRUMENT NUMBER	MAXIMUM RECORDED
NOWIDER	READING (EL ft)
P-1	403.5
P-2	388.2
P-3	384.7
P-4	380.8
P-5	364.1
P-6	391.4
P-7	388.7
P-8	364.2
PA-1	326.0
PA-2	324.6
PA-4	403.5
PA-5	287.9
PA-6*	n/a
PA-7*	n/a
PA-8**	n/a
PA-9	295.0
PA-10	295.0
PA-11	361.6
EX-1	398.3
EX-2	417.4
EX-3	281.8
EX-4*	n/a

^{*}Damaged casing, no longer in service

^{**}Dry, no longer monitored